

Single Mount Panel Mount SSRs

Continental Part	Input Signal	Output Voltage	Output Current	Comment
Zelio Cross Reference	Input Signal	Output Voltage	Output Current	Comment
SVDA-3V10	4-32Vdc	24-330Vac	10A	
SSP1A110BDT	3-32Vdc	24-300Vac	10A	
SVDA-3V25	4-32Vdc	24-330Vac	25A	
SSP1A125BDT	3-32Vdc	24-300Vac	25A	
SVDA-3V50	4-32Vdc	24-330Vac	50A	
SSP1A150BDT	3-32Vdc	24-300Vac	50A	
SVDA-3V75	4-32Vdc	48-660Vac	50A	
SSP1A450BDT	3-32Vdc	48-660Vac	50A	
SVDA-6V50	4-32Vdc	24-330Vac	75A	
SSP1A175BDT	3-32Vdc	24-300Vac	75A	
SVDA-6V75	4-32Vdc	48-660Vac	75A	
SSP1A475BDT	3-32Vdc	48-660Vac	75A	
SSP1A490BDT	3-32Vdc	48-660Vac	90A	
SSP1A4125BDT	3-32Vdc	48-660Vac	125A	
SVAA-3V10	100-280Vac	24-330Vac	10A	
SSP1A110M7T	90-280Vac	24-300Vac	10A	
SVAA-3V25	100-280Vac	24-330Vac	25A	
SSP1A125M7T	90-280Vac	24-300Vac	25A	
SVAA-3V50	100-280Vac	24-330Vac	50A	
SSP1A150M7T	90-280Vac	24-300Vac	50A	
SVAA-3V75	100-280Vac	48-660Vac	50A	
SSP1A450M7T	90-280Vac	48-660Vac	50A	
SVAA-6V50	100-280Vac	24-330Vac	75A	
SSP1A175M7T	90-280Vac	24-300Vac	75A	
SVAA-6V75	100-280Vac	48-660Vac	75A	
SSP1A475M7T	90-280Vac	48-660Vac	75A	
SSP1A490M7T	90-280Vac	48-660Vac	90A	
SSP1A4125M7T	90-280Vac	48-660Vac	125A	
SVDD-1V12	3.5-32Vdc	3-150Vdc	12A	
SSP1D412BDT	3.5-32Vdc	3-150Vdc	12A	
SVDD-1V20	3.5-32Vdc	3-150Vdc	20A	
SSP1D425BDT	3.5-32Vdc	3-150Vdc	25A	
SVDD-1V40	3.5-32Vdc	3-150Vdc	40A	
SSP1D440BDT	3.5-32Vdc	3-150Vdc	40A	

Notes

1. Continental amperage ratings for single phase panel mount SSRs are based on an ambient environment of 40°C. Zelio amperage ratings for single phase panel mount

Always make certain that panel mount SSRs are mounted to the appropriate heat sink